

## AMI pH/Redox (QV-Flow)

*On-line Analyzer for the Continuous Measurement of pH or Redox (ORP) in High Purity Water, Steam and Condensate.*

- Simultaneous measurement of pH or redox, sample temperature and sample flow.
- Combined or separated sensors with reference electrodes for various sample conditions.
- Flow cell QV-Flow IS1000 made of stainless steel.
- Complete system mounted on a stainless steel panel.
- Factory tested, ready for installation and operation.

Data Sheet No: DenA2122XXXX



pH and Redox

# pH and Redox (ORP) in High Purity Water, Steam and Condensate



## Transmitter AMI pH/Redox

- Rough Aluminum housing IP66.
- Measuring range: 1 to 13 pH, or -500 to +1500 mV depending on installed sensor.
- Temperature compensation according to:
  - Nernst (for potable water and waste water).
  - Nernst with non-linear solution compensation (for high purity water).
  - Nernst with linear compensation with selectable coefficient (for high purity water).
- Two freely scalable current signal outputs (0/4-20 mA), third one as an option.
- Optional fieldbus communication board.

## Sensors

- Swansensor ST/AY:  
pH 1 to 13 resp. -400 to +1200 mV  
Swansensor SI/FL:  
pH 1 to 12 resp. -500 to +1500 mV  
Resolution:  
0.01 pH or 1 mV

## Flow Cell QV-Flow

- Flow cell QV-Flow IS 1000 made of stainless steel with quick release vessel, needle valve, digital sample flow meter and temperature sensor.
- Flow rate: 5 to 10 l/h
- Inlet pressure: 0.2 to 2 bar



**swan**  
ANALYTICAL INSTRUMENTS